

1A1G~1A7G

GLASS PASSIVATED JUNCTION RECTIFIER

VOLTAGE	50 to 1000 Volt	CURRENT	1.0 Ampere
----------------	------------------------	----------------	-------------------



R-1 Unit:mm

FEATURES

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability
- High current capability

MECHANICAL DATA

- Case Material: Molded Plastic.
- UL Flammability Classification Rating 94V-0



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	1A1G	1A2G	1A3G	1A4G	1A5G	1A6G	1A7G	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Current (see FIG.1)	$I_{F(AV)}$	1.0							A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	30							A
Maximum Forward Voltage at 1 A	V_F	1.1							V
Maximum DC Reverse Current at Rated DC Blocking Voltage $T_J = 25^{\circ}C$ $T_J = 100^{\circ}C$	I_R	1.0 50							μA
Typical Junction Capacitance	C_J	15							pF
Thermal Resistance	$R_{\theta JA}$	50							$^{\circ}C / W$
Operating Junction Temperature Range	T_J	-55 to +125							$^{\circ}C$
Storage Temperature Range	T_{STG}	-55 to +150							$^{\circ}C$

Notes: 1. Measured at 1 MHz and Applied Reverse Voltage of 4.0 V D.C.

2. Thermal resistance from junction to ambient, and from junction to lead at 0.375" (9.5mm) lead length.

1A1G~1A7G

RATINGS AND CHARACTERISTIC CURVES




Fig.1 FORWARD CURRENT DERATING CURVE




Fig.2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




Fig.3 TYPICAL REVERSE CHARACTERISTICS




Fig.4-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




Fig.5 TYPICAL JUNCTION CAPACITANCE

1A1G~1A7G

Ordering Information

- **Packing information**

1A1G~1A7G	Packing Quantity
Tape&Reel	13 Inch; 5kpcs/Reel
Ammo Packing	5kpcs/Ammo Box
Bulk(Tube/Box)	1kpcs/Box