

UF5400G~UF5408G

GLASS PASSIVATED JUNCTION ULTRA FAST RECOVERY RECTIFIER

VOLTAGE 50 to 1000 Volt **CURRENT** 3 Ampere



DO-201AD Unit:mm

FEATURES

- Low Forward Voltage Drop and Low Leakage
- Ultra Fast Switching Speed For High Efficiency
- Halogen free available upon request by adding suffix "-HF"

MECHANICAL DATA

- Case Material: Molded Plastic.
- UL Flammability Classification Rating 94V-0




MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	UF5400G	UF5401G	UF5402G	UF5404G	UF5406G	UF5407G	UF5408G	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RM S Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC B locking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forw ard Current (see FIG.2)	I _{F(AV)}	3							A
Peak Forward Surge Current : 8.3ms single half sine-w ave superimposed on rated load	I _{FSM}	100							A
Maximum Forward Voltageat 3A	V _F	1.0			1.3	1.7			V
Maximum DC Reverse Current at at Rated DC Blocking Voltage T _J =25°C T _J =100°C	I _R	10 200							μA
Typical Junction Capacitance	C _J	7.5				5.0			pF
Maximum Reverse Recovery Time	t _{rr}	50				7.5			ns
Operating and Storage Temperature Range	T _J ,T _{STG}	-55 to + 150							°C


UF5400G~UF5408G

Figure 1
Typical Forward Characteristics




Instantaneous Forward Current - Amperes *versus*
Instantaneous Forward Voltage - Volts

Figure 2
Forward Derating Curve



Average Forward Rectified Current - Amperes *versus*
Ambient Temperature - °C

Figure 3
Junction Capacitance



Junction Capacitance - pF *versus*
Reverse Voltage - Volts

UF5400G~UF5408G

Ordering Information

- Packing information

UF5400G~UF5408G	Packing Quantity
Tape&Reel	13 Inch; 1.25kpcs/Reel
Ammo Packing	1.25kpcs/Ammo Box
Bulk(Tube/Box)	0.5kpcs/Box