

MCL4148

FAST SWITCHING SURFACE MOUNT DIODES

VOLTAGE 100 Volts **POWER** 500 mWatts



MICRO-MELF Unit : inch (mm)

FEATURES

- Fast switching Speed.
- Surface Mount Package Ideally Suited For Automatic Insertion.
- Silicon Epitaxial Planar Construction.
- Lead free in compliance with EU RoHS 2011/65/EU directive

MECHANICAL DATA

- Case: MICRO MELF, Glass
- Terminals: Solderable per MIL-STD-750, Method 2026
- Polarity: Cathode Band
- Marking: Cathode Band Only



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

PARAMETER	SYMBOL	MCL4148	UNITS
Peak Reverse Voltage	V_{RM}	100	V
Maximum Average Forward Current at Ta=25 °C And f≥50Hz	$I_{F(AV)}$	150	mA
Surge Forward Current at t < 1s and Tj= 25 °C	I_{FSM}	500	mA
Power Dissipation at Tamb= 25 °C	P_{TOT}	500	mW
Maximum Forward Voltage at $I_F=10mA$	V_F	1.0	V
Maximum Leakage Current at $V_R=20V$ at $V_R=75V$ at $V_R=20V, T_J= 150°C$	I_R	25 5 50	nA μA μA
Maximum Capacitance at $V_F=V_R=0$	C_J	4	pF
Maximum Reverse Recovery Time From $I_F=-I_R=10mA$ to $I_{RR}=-1mA, V_R=6V, R_L=100 \Omega$	t_{rr}	4	ns
Typical Thermal Resistance	$R_{\theta JA}$	300	°C / W
Junction Temperature and Storage Temperature Range	T_J, T_S	-65 to +175	°C

NOTE:

1. CJ at VR=0, f=1MHZ

MCL4148

RATING AND CHARACTERISTIC CURVES




Fig.1 ADMISSIBLE REPETITIVE PEAK FORWARD CURRENT VERSUS PULSE DURATION




Fig.2-DYNAMIC FORWARD RESISTANCE VERSUS FORWARD CURRENT




Fig.3 FORWARD CHARACTERISTICS




Fig.4 DERATING CURVE





Fig.5 TYPICAL JUNCTION CAPACITANCE

MCL4148

MOUNTING PAD LAYOUT

MICRO-MELF

Unit: inch (mm)



ORDER INFORMATION

- Packing information

T/R - 10K per 13" plastic Reel

T/R - 3K per 7" plastic Reel

MCL4148

Part No_packing code_Version


MCL4148_R1_10001

MCL4148_R2_10001

For example :

RB500V-40_R2_00001

Part No.



Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Siyang Grande Electronics Co., Ltd..
- Siyang Grande Electronics Co., Ltd. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Siyang Grande Electronics Co., Ltd. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Siyang Grande Electronics Co., Ltd. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Siyang Grande Electronics Co., Ltd. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Siyang Grande Electronics Co., Ltd. for any damages resulting from such improper use or sale.
- Since Grande uses lot number as the tracking base, please provide the lot number for tracking when complaining.