

US2AA~US2MA

SURFACE MOUNT ULTRAFAST RECTIFIER

VOLTAGE 50 to 1000 Volt **CURRENT** 2 Ampere



SMA / DO-214AC Unit:mm

FEATURES

- Ultra-Fast Recovery Time for High Efficiency
- Glass Passivated Junction
- High Current Capability
- Moisture Sensitivity Level 1
- Lead free in compliance with EU RoHS 2.0

MECHANICAL DATA

- Case Material: Molded Plastic.
- UL Flammability Classification Rating 94V-0



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	US2AA	US2BA	US2DA	US2GA	US2AJ	US2KA	US2MA	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Current (see FIG.1)	I _{F(AV)}	2							A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	50							A
Maximum Forward Voltage at 1 A	V _F	1.0			1.4	1.7			V
Maximum DC Reverse Current at Rated DC Blocking Voltage T _J =25°C T _J =125°C	I _R	5 350							uA
Maximum Reverse Recovery Time(Note 1)	t _{rr}	50				75			ns
Thermal Resistance	R _{θJL}	30							°C / W
Typical Junction Capacitance (Note2)	C _J	28							pF
Operating Junction Temperature Range	T _J	-55 to +150							°C
Storage Temperature Range	T _{STG}	-55 to +150							°C

NOTES:

1. Reverse Recovery Test Conditions: $I_F=0.5A$, $I_R=1.0A$, $I_{rr}=0.25A$
2. Measured at 1.0MHz and applied reverse voltage of 4.0 volt

US2AA~US2MA

RATING AND CHARACTERISTIC CURVES




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Forward Surge Current Derating Curve




Fig. 4 Typical Reverse Characteristics




Fig. 5 Reverse Recovery Time Characteristic and Test Circuit





Fig. 6 Typical Junction Capacitance

US2AA~US2MA

MOUNTING PAD LAYOUT

SMA / DO-214AC

Unit:Inch(mm)



ORDER INFORMATION

- Packing information

Part Number	Case	Reel Size	QUANTITY
US2AA~US2MA	SMA	13 Inch	5000