

ABS202~ABS207

BRIDGE RECTIFIERS


VOLTAGE 200 to 1000 Volt **CURRENT** 2.0 Ampere

FEATURES

- Glass Passivated Diode Construction
- Ideal for printed circuit board
- High surge current capability
- Lead free in compliance with EU RoHS

MECHANICAL DATA

- Case Material: Molded Plastic.
- UL Flammability Classification Rating 94V-0



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	ABS202	ABS204	ABS205	ABS206	ABS207	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	200	400	600	800	1000	V
Maximum Average Forward Current (see FIG.1)	$I_{F(AV)}$	2.0					A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	50					A
Maximum Forward Voltage at 1.0 A	V_F	0.95					V
Maximum DC Reverse Current at $T_J = 25^\circ\text{C}$ Rated DC Blocking Voltage	I_R	10					μA
Thermal Resistance(Note1)	$R_{\theta JA}$	62.5					$^\circ\text{C} / \text{W}$
Operating Junction Temperature Range	T_J	-55 to +150					$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150					$^\circ\text{C}$

Notes: 1. Device mounted P.C.B with 0.47x0.47"(12mmx12mm) Copper Pads.

ABS202~ABS207

RATING AND CHARACTERISTIC CURVES

FIG.1-TYPRCAL FORWARD CURRENT DERATING CURVE




Fig.1 FORWARD CURRENT Derating Curve

FIG.2-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




Fig.2 Max Non-Repetitive Peak Forward Surge Current




Fig.3 Typ Forward Characteristics




Fig.4 Typical Reverse Characteristics per element

FIG.5-TYPICAL REVERSE CHARACTERISTICS

PERCENT OF RATED PEAK REVERSE VOLTAGE(%)

ABS202~ABS207

ORDER INFORMATION

- Packing information

Part Number	Case	DELIVERY MODE	QUANTITY
ABS202~ABS207	ABS	13 Inch	5000/Reel