

GBL2005~GBL210

BRIDGE RECTIFIERS


VOLTAGE	50 to 1000 Volt	CURRENT	2 Ampere
----------------	------------------------	----------------	-----------------

FEATURES

- High case dielectric strength
- Glass passivated chip junction
- High surge current capability
- Lead free in compliance with EU RoHS

MECHANICAL DATA

- Case Material: Molded Plastic.
- UL Flammability Classification Rating 94V-0



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	GBL2005	GBL201	GBL202	GBL204	GBL206	GBL208	GBL210	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Current (see FIG.1)	$I_{F(AV)}$	2							A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	80							A
Maximum Forward Voltage at 1.0 A	V_F	1.05							V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	10							μA
Thermal Resistance	$R_{\theta JA}$	47							$^{\circ}C / W$
Operating Junction Temperature Range	T_J	-55 to +150							$^{\circ}C$
Storage Temperature Range	T_{STG}	-55 to +150							$^{\circ}C$

GBL2005~GBL210

RATING AND CHARACTERISTIC CURVES

Fig. 1 - FORWARD CURRENT DERATING CURVE




Fig. 2 - Surge Forward Current Capability




Fig. 3 - TYPICAL FORWARD CHARACTERISTICS





FIG.4-TYPICAL REVERSE CHARACTERISTICS



GBL2005~GBL210

ORDER INFORMATION

- Packing information

Part Number	Case	DELIVERY MODE	QUANTITY
GBL2005~GBL210	GBL	BULK	6000/Ctn