

SK22~SK210

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

VOLTAGE	20 to 100 Volt	CURRENT	2 Ampere
---------	----------------	---------	----------



SMB/ DO-214AA Unit:mm

FEATURES

- Low power loss, High efficiency
- High surge capacity
- High current capacity, low V_F
- Lead free in compliance with EU RoHS 2.0

MECHANICAL DATA

- Case Material: Molded Plastic.
- UL Flammability Classification Rating 94V-0



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	SK22	SK23	SK24	SK25	SK26	SK28	SK210	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	80	100	V
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	56	70	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	80	100	V
Maximum Average Forward Current	I _{F(AV)}	2							A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	50							A
Maximum Forward Voltage at 2 A	V _F	0.50			0.70		0.85		V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I _R	2							mA
Thermal Resistance	R _{θJL} R _{θJA}	15 71							°C / W
Typical Junction Capacitance	C _J	230					50		pF
Operating Junction Temperature Range	T _J	-55 to +125							°C
Storage Temperature Range	T _{STG}	-55 to +150							°C

SK22~SK210

RATING AND CHARACTERISTIC CURVES

FIG.1: FORWARD CURRENT DERATING CURVE




FIG2: Surge Forward Current Capability




FIG.3: TYPICAL FORWARD CHARACTERISTICS





FIG.4: TYPICAL REVERSE CHARACTERISTICS




SK22~SK210

MOUNTING PAD LAYOUT

SMB / DO-214AA

Unit:Inch(mm)



ORDER INFORMATION

- Packing information

Part Number	Case	Reel Size	QUANTITY
SK22~SK210	SMB	13 Inch	3000