

SK32~SK310

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

VOLTAGE	20 to 100 Volt	CURRENT	3 Ampere
---------	----------------	---------	----------



SMC / DO-214AB Unit:mm

FEATURES

- Low power loss, High efficiency
- High surge capacity
- High current capacity, low V_F
- Lead free in compliance with EU RoHS 2.0

MECHANICAL DATA

- Case Material: Molded Plastic.
- UL Flammability Classification Rating 94V-0



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	SK32	SK33	SK34	SK35	SK36	SK38	SK310	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	20	30	40	50	60	80	100	V
Maximum RMS Voltage	V_{RMS}	14	21	28	35	42	56	70	V
Maximum DC Blocking Voltage	V_{DC}	20	30	40	50	60	80	100	V
Maximum Average Forward Current	$I_{F(AV)}$	3							A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	100							A
Maximum Forward Voltage at 3 A	V_F	0.50		0.75		0.85			V
Maximum DC Reverse Current at Rated DC Blocking Voltage $T_J=25^{\circ}C$ $T_J=100^{\circ}C$	I_R			0.5 20					mA
Thermal Resistance	$R_{\theta JA}$ $R_{\theta JL}$			80 10					$^{\circ}C / W$
Typical Junction Capacitance	C_J			250					pF
Operating Junction Temperature Range	T_J			-55 to +150					$^{\circ}C$
Storage Temperature Range	T_{STG}			-55 to +150					$^{\circ}C$

SK32~SK310

RATING AND CHARACTERISTIC CURVES




FIG.1 FORWARD CURRENT DERATING CURVE




FIG.2 MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 TYPICAL FORWARD CHARACTERISTICS





FIG.4 TYPICAL REVERSE CHARACTERISTICS

SK32~SK310

MOUNTING PAD LAYOUT

SMC / DO-214AB

Unit:Inch(mm)



ORDER INFORMATION

- Packing information

Part Number	Case	Reel Size	QUANTITY
SK32~SK310	SMC	13 Inch	3000