

ER3A~ER3M

SURFACE MOUNT SUPERFAST RECTIFIER

VOLTAGE 50 to 1000 Volt **CURRENT** 3 Ampere



SMC / DO-214AB Unit:mm

FEATURES

- Superfast Recovery Times For High Efficiency
- Glass Passivated Junction
- Easy Pick And Place
- Moisture Sensitivity Level 1
- Lead free in compliance with EU RoHS 2.0

MECHANICAL DATA

- Case Material: Molded Plastic.
- UL Flammability Classification Rating 94V-0



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	ER3A	ER3B	ER3D	ER3G	ER3J	ER3K	ER3M	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Current (see FIG.1)	I _{F(AV)}	3							A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	100							A
Maximum Forward Voltage at 3 A	V _F	1.0			1.25	1.70			V
Maximum DC Reverse Current at Rated DC Blocking Voltage T _J =25°C T _J =100°C	I _R	5.0 200							uA
Maximum Reverse Recovery Time(Note 1)	t _{rr}	35					75		ns
Thermal Resistance	R _{θJL}	16							°C / W
Typical Junction Capacitance (Note2)	C _J	45							pF
Operating Junction Temperature Range	T _J	-55 to +150							°C
Storage Temperature Range	T _{STG}	-55 to +150							°C

NOTES:

1. Reverse Recovery Test Conditions: $I_F=0.5A$, $I_R=1.0A$, $I_{rr}=0.25A$
2. Measured at 1.0MHz and applied reverse voltage of 4.0 volt

ER3A~ER3M

RATING AND CHARACTERISTIC CURVES




Fig. 1 Forward Current Derating Curve




Fig. 3 Surge Current Derating Curve




Fig. 5 Typical Junction Capacitance




Fig. 2 Typical Forward Characteristics




Fig. 4 Typical Reverse Characteristics





Fig. 6 Reverse Recovery Time Characteristic and Test Circuit

ER3A~ER3M

MOUNTING PAD LAYOUT

SMC / DO-214AB

Unit:Inch(mm)



ORDER INFORMATION

- Packing information

Part Number	Case	Reel Size	QUANTITY
ER3A~ER3M	SMC	13 Inch	3000